

SEAL Wearable GPS Tracker

LoRaWAN® connected GPS Tracker for Locating Personnel

SEAL is an ideal solution for tracking your personnel working remotely in the field. This device provides GPS enabled, near real-time satellite location tracking with LoRaWAN®. The rugged IP67 design allows for operation in diverse deployment environments, with an operable temperature range of -20°C to +60°C and BLE integration for continued tracking indoors. SEAL provides up to 15 months of battery life. SEAL is designed to identify fall and impact detection for enhanced worker safety. The SEAL wearable Tracker is seamlessly integrated with TEKTELIC's End-to-End IoT solution.



Technical and Functional System Specifications

General System Parameters

| Operational Temperature | -20°C to +60°C | |
|---------------------------|------------------|--|
| Protection Rating | IP67 | |
| Size without safety clip* | 104 x 70 x 34 mm | |
| Size with safety clip* | 104 x 70 x 56 mm | |
| Battery | 3x AA (LiFeS2) | |
| Battery Life | 15 Months | |

^{*} Excluding belt & strap clips

LoRa Parameters

| RF Power | 14 dBm | |
|-------------------|------------------------|--|
| RF Sensitivity | -137dBm (SF12, 125kHz) | |
| ISM Band | All Global ISM Bands | |
| Antenna | Internal | |
| LoRa Device Class | Class A | |

GNSS Features

| Position Accuracy | 5 m | |
|-----------------------------|----------------------------------|--|
| TTFF (Time to First Fix) | Cold Start - 30 Seconds | |
| | Hot Start - 1 Second | |
| Sensitivity | -167 dBm tracking and navigation | |
| | -160 dBm reacquisition | |
| | -148 dBm cold start | |
| | -159 dBm hot start | |

Key Features

| 33 | Fall Detection |
|----|----------------|
| | |

Optional Harness Detection

Precise GPS & Integrated BLE

GNSS Datalogging

Data Transmission over LoRaWAN **>>**

Event-Based Startup

Geofencing Capabilities **>>**

Audio & Visual Alarms **>>**

>> 15 Months Battery Life

Rugged IP67 Design

Regulatory Compliance

| Safety | (CE) EN IEC 62368-1:2020 (Ed. 3) | |
|------------|----------------------------------|------------|
| Regulatory | ETSI EN 300 220 | |
| | ETSI EN 301-489-1/-3 | |
| | FCC 15.247 | FCC 15.209 |
| | RSS-247 | RSS-GEN |





+1.403.338.6900



WWW.TEKTELIC.COM

TEKTELIC Communications is a premier supplier of best-in-class LoRaWAN® IoT Gateways, Sensors, and Custom Applications. These elements combined provide a powerful end-to-end solution that can be easily, quickly, and cost effectively deployed to address the most demanding IoT challenges.