

## Senstick Temperature Probe STP30

Senstick is an award-winning LoRaWAN sensor. It is designed to operate autonomously for up to 7 years in harsh environments. It is suitable for wide variety of applications where reliable and case specific solution is needed. STP20 is a cost-effective temperature probe sensor.

### Key features

- Harsh environments
- Rigidized housing
- Easy installation
- Motion detection
- NFC configuration

### Applications

- Mulch temperature
- Soil temperature
- Rail tracks temperature
- Water temperature



## Technical specification

Enclosure	
Weight	160g w/ batteries / 220 g with batteries
Dimensions	Casing: 18mm x 230mm / Probe: 5mm x 50mm
Cable length	1.5 m or custom length
Materials	UV stable plastic, ALU casing
IP rating	IP68
Operating conditions	
Temperature	-40°C to +85°C
Humidity	0 to 100% RH
Power supply	
Battery type	2 x 1.5V AAA Alkaline
Expected operation	<7 years (depending on sampling, signal, environment)
Configuration	
Sending interval	Configuration via NFC and downlink
Data upload interval	Configuration via NFC and downlink
NFC configuration	<a href="#">Native Android App</a>

## Connectivity

Wireless Technology	LoRaWAN® 1.0.3
Wireless Security	LoRaWAN® End-to-End encryption (AES-CTR), Data Integrity Protection (AES-CMAC)
LoRaWAN Device Type	Class A - End-device
Supported regions	US902–928, EU863–870, AS920-923, AU915–928
Link Budget	137dB (SF7) to 151dB (SF12)
RF Transmit Power	14dBm (Region specific)

## Sensors

### Temperature Probe

Range	-55°C to +125°C
Accuracy	±0.5°C

### Acceleration

Range	±2g to ±16g
-------	-------------

## Accessories

MPOM10	Snap-on mounting kit, suitable for indoor use
MABS10	ABS mounting kit. Installation with two screws for indoor and outdoor use
MALU10	Rigidized ALU mounting kit. Installation with two screws for indoor and outdoor use.

