Antenna-Port-N

Für Labor- und Testzwecke vorgesehen

Direkt montierbare Stabantenne für 5G, LTE, UMTS, GSM und WLAN. Lineare Antenne mit vertikaler Polarisation

Hauptmerkmale

Cellular	5G / LTE / UMTS / GMS
WiFi / WLAN	2.4 / 5GHz
Erforderliche Anzahl	5G-NR, 4x Antenna-Port-N
	4G-LTE, 2x Antenna-Port-N
	WiFi/WLAN mit 2x2 MIMO, 2x Antenna-Port-N

Spezifikation

Mobile / Cellular	**Standard**	1 x 5G / LTE / UMTS / GSM **5G** Bands: 1, 2, 3, 5, 7, 8, 12, 20, 25, 28, 65, 66, 71, 80, 81, 82, 83, 84, 86 - TDD Bands: 34, 38, 39, 40, 41, 78 **Frequency (MHz)** -
	Specification	**Impedance** 50 Ohm
	Connectors	1x SMA male
WiFi / WLAN	**Standards**	1 x Dual-band WLAN 2.4/5 GHz **Frequency (MHz)** 2400 - 2500, 5100 - 5875
	Specification	**Impedance** 50 Ohm
	Connectors	1x SMA male
Mechanical	**Dimensions**	**Diameter** 27 mm **Height** 196 mm
	Weight	50 g
	Mounting	Device
	Color	black
Environment	**Operating Temperature**	-10°C bis +55°C
Certifications	**Compliance**	Intended for laboratory and test purposes only
	Domain	Industrial
Other	**Order Code**	Antenna-Port-N

www.netmodule.com Switzerland +41 31 985 25 10
sales@netmodule.com Germany +49 6196 77 99 79 0

NetModule AG Maulbeerstrasse 10
Switzerland 3011 Bern

Hirschmann Automation & Control GmbH
Germany

Frankfurter Str. 10-14
65760 Eschborn